Position switch with spring rod
RF 96 TK SW917-NET
Material no.: on request

Product features

- sWave.NET® wireless technology
- Thermoplastic enclosure
- Mounting details to EN 50047
- No wiring and pipe laying required
- Power supply by Lithium battery (replaceable)
- Configurable online via wireless interface
- Actuator: Spring rod with plastic tip TK

Notes
- The battery must be ordered separately

Dimensions



General technical data

Applied standards
EN 60947-5-1, EN 61000-6-2, EN 61000-6-3, EN 61000-4-2, EN 301 489-1, EN 301 489-3, EN 300 220-1, EN 300 220-2

Enclosure
thermoplastic, glass-fibre reinforced, shockproof, self-extinguishing UL 94 V-0

Tightening torque
M4 enclosure mounting screws: max 1.2 Nm
M2.5 cover screws: approx. 0.45 Nm

Degree of protection
IP67 (IEC/EN 60529)

Ambient temperature
–20 °C ⋯ +65 °C

Operation cycles
max. 12000 telegrams with repetitions/h

Mechanical life
> 1 million operations

Actuating time
min. 80 ms

Note
transmission of battery voltage and switching condition

Wireless approvals
Brazil: ANATEL 04172-18-06718

Wireless technology

Protocol
sWave.NET®

Frequency
917 MHz (Brazil)

Errors and omissions excepted.

Position switch with spring rod
RF 96 TK SW917-NET
Material no.: on request

Wireless technology (contd.)

Transmission power
< 25 mW

Data rate
66 kbps

Channel bandwidth
550 kHz

Wireless range
max. 450 m outdoors, max. 40 m indoors

Voltage supply

Voltage source
lithium battery Tadiran TL-5920 (replaceable), alternatively SL-2770

System
$Li/SOCl_2$

Nominal voltage
3.6 V

Nominal capacity
8.5 Ah

Alternative voltage supply

Voltage source
lithium battery Tadiran SL-2770 (replaceable)

System
$Li/SOCl_2$

Nominal voltage
3.6 V

Nominal capacity
8.5 Ah

Battery life
depending on the switching frequency, at 6x/minute: > 10 years

Errors and omissions excepted.